

- **FSI660R** 80-3/4"L x 48-1/8"D x 60-1/8"H
- **FSI860R** 99-3/4"L x 48-1/8"D x 60-1/8"H

Included

- Breeze self-contained refrigeration
- Compressor air intake in one side & out other side. All louvered panels cannot be blocked
- LED 4000K top light(s)
- One year parts & labor; 5 year compressor warranty
- Price tag molding (matches interior color)
- Removable deck pans provide complete access to evaporator coil & refrigeration connections
- Vinyl T-edge (matches interior color)
- Warmest average product temperature of 40°F or less




Specify	Standard Features	Additional Options
EXTERIOR COLOR	• Powder coated Black Texture	• Laminate (stock/non-stock colors) • Stainless steel
INTERIOR COLOR	• Powder coated Silversan Black	• Stainless steel
LOWER FRONT PANEL COLOR	• Powder coated Black Texture	• Stainless steel (must choose stainless exterior)
BASE SUPPORT	• Casters w/ levelers	• Levelers (remote)
SHELVING	• Non-adjustable metal shelves, non-lighted	• Non-adjustable metal shelves, lighted (LED 4000K)
ELECTRICAL CONNECTION	• 6' Straight blade power cord (self-cont.)	• 6' Locking power cord (self-cont.) • Electrical leads (remote)
REFRIGERATION	• Breeze self-contained refrigeration	1 • Remote w/thermostat, solenoid & TXV
MISCELLANEOUS		• Second year parts & labor warranty (excludes compressor)

Option Notes: 1 - Read important notes for remote options


Intended Environment: Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.

Zone	Intended Product To Be Displayed	Warmest Avg Prod Temp ° F
1	Packaged refrigerated products-Prechilled to Warmest Avg Prod Temp.	40

PLAN VIEW



SIDE VIEW



NOTE: ALL DIMENSIONS APPROXIMATE

- ⊗ ELECTRICAL JUNCTION BOX
(SUPPLIED WITH 6\"

- ⊕ REFRIGERATION LINE CONNECTION.
Ⓜ REMOTE FLOOR SINK & UTILITIES
ACCESS AREA.

- ⊞ SELF-CONTAINED CASE SERVICE ACCESS AREA.
⊞ DRY CASE SERVICE ACCESS AREA.

Model Technical Specifications														
Model	L"	L1"	L2"	System Circuit Volts			Phs	Freq	Amps ***	Watts	Wires	NEMA Plug	SST	Conv. Rack BTU/H
FSI660R	N/A	80.75	30.00	Remote (DX)	Circuit #1	110-120	1	50-60	5.00	285	2+G	Leads Single	20.00	13478
				Self-Contained (R290)	Circuit #1	208-240	1	50-60	24.00	5,662	2+G	6-30P or L6-30P	N/A	N/A
FSI860R	N/A	99.75	38.00	Remote (DX)	Circuit #1	110-120	1	50-60	6.00	351	2+G	Leads Single	20.00	14688
				Self-Contained (R290)	Circuit #1	208-240	1	50-60	24.00	5,729	2+G	6-30P or L6-30P	N/A	N/A
														Para. Rack BTU/H
														Est Wt

*** Does not include electric defrost on freezer models.

Regulatory Approvals:

All Models
 Accordance with AHRI Std 1200
 ETL Listed to UL 60335-2-89
 ETL Sanitation to NSF/ANSI 7



In Accordance with
AHRI Std 1200

DOE 2017
 Energy Efficiency
 Compliant

Important Notes:

- 1) REMOTE REFRIGERATION NOTE: Condensing unit not included, floor drain required.
- 2) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle
- 3) NOTE: Electrical specs reflect highest Amp draw using lighted shelves option

⚠ WARNING: This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.